NSN 5905-00-688-4520

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-688-4520 **Section Quantity:** 1 **Body Style:** Rectangular **Reliability Indicator:** Not established **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.125 inches **Body Length:** 0.328 inches **Body Width:** 0.783 inches **Body Height:** 0.875 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Fragility Factor:** Moderately rugged **Terminal Location:** Front end **Mounting Method:** Tab **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 1.5 megohms single section **Rotary Actuator Travel In Angular Deg:** 300.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section

Stops

Actuator Travel Control Feature:

NSN 5905-00-688-4520

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient	Tempurature	In Deg	g Celsius	Per S	ection A	At Full	Rated	Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0