## NSN 5905-00-688-4677

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-688-4677 **Section Quantity:** 2 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.3125 inches **Mounting Hole Diameter:** 0.062 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.0625 inches **Body Length:** 1.250 inches **Body Width:** 0.500 inches **Body Height:** 0.313 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:** 7.50 inch-ounces **Maximum Running Torque:** 7.50 inch-ounces **Maximum Stop Torque:** 20.00 inch-ounces **Lateral Distance Between Mounting Hole Centers: Mounting Facility Quantity:** 

1.000 inches 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole

## NSN 5905-00-688-4677

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Cubic Measure:
0.196 cubic inches
Electrical Resistance Per Section:
100.000 ohms all sections
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
135.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
50.0 to 50.0 all sections
Power Dissipation Rating Per Section In Watts:
0.5 free air all sections
Resistance Tolerance Per Section In Percent:
10.0 to 10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 wire lead
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0