

View Online at <https://aerobasegroup.com/nsn/5905-00-688-7012>

**Section Quantity:**

4

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.7500 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

1.765 inches

**Undercut Diameter:**

1.720 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

2.000 inches

**Angle Of Mounting Hole In Deg:**

90.0

**Angle Between Centerlines Of Mounting Holes In Deg:**

120.0

**Shaft Diameter:**

0.249 inches

**Shaft Length:**

0.562 inches

**Body Length:**

1.766 inches

**Overall Diameter:**

2.000 inches

**Mounting Lip Diameter:**

1.7820 inches

**Mounting Lip Depth:**

0.0620 inches

**Mounting Hole/stud Circle Diameter:**

1.250 inches

**Shaft Style:**

Round

**Actuator Type:**

Double ended shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

355.0

**Maximum Starting Torque:**

5.00 inch-ounces

**Maximum Running Torque:**

4.00 inch-ounces

**Screw Thread Diameter:**

0.164 inches

**Screw Thread Series Designator:**

Unc

**Screw Thread Qty Per Inch (tpi):**

32.0

**Mounting Facility Quantity:**

3

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Threaded hole

**Electrical Resistance Per Section:**

2.500 percent, rated amperes c and better v.G. Stepping

**Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:**

177.0 1st section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.15/+0.15 all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 all sections

**Power Dissipation Rating Per Section In Watts:**

3.0 free air all sections

**Fixed Tap Quantity Per Section:**

1 1st section

**Tap Location Tolerance Per Section:**

-0.5/+0.5 degrees angular rotation 1st section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

All sections linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 all sections

**Terminal Type And Quantity:**

13 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0