## NSN 5905-00-688-7013

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-688-7013 **Section Quantity:** 3 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 4.687 inches **Undercut Diameter:** Between 2.374 inches and 2.375 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 2.500 inches **Shaft Diameter:** Between 0.1871 inches and 0.1874 inches **Shaft Length:** 0.688 inches **Body Length:** 3.437 inches **Mounting Lip Diameter:** 2.5000 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Double ended shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:** 8.00 inch-ounces **Maximum Running Torque:** 

0.60 inch-ounces **Shaft End Play:**0.00500 inches

## NSN 5905-00-688-7013

**Shaft Runout:** 

Precision Wire Wound Variable Resistor - Page 2 of 3



0.001 inches						
Lateral Runout:						
0.002 inches						
Pilot Diameter Runout:						
0.00100 inches						
Shaft Radial Play:						
0.002 inches						
Mechanical Backlash In Deg Angular Rotation:						
0.25						
Terminal Location:						
Radially positioned over less than half the circumference						
Mounting Method:						
Clamp ring						
Electrical Resistance Per Section:						
30.000 percent, rated amperes c and better finish						
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:						
90.0 1st section and 180.0 1st section and 270.0 1st section						
Rotary Actuator Travel In Angular Deg:						
360.0						
Function Conformity Tolerance Per Section:						
-0.50/+0.50 3rd section						
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:						
125.0 all sections						
Power Dissipation Rating Per Section In Watts:						
3.0 free air all sections						
Function Conformity Per Section:						
All sections absolute linearity						
Fixed Tap Quantity Per Section:						
2 1st section						
Tap Location Tolerance Per Section:						
-1.0/+1.0 degrees angular rotation 1st section						
Resistance Tolerance Per Section In Percent:						
-5.0/+5.0 3rd section						
Actuator Travel Control Feature:						
Continuous motion						
Function Characteristic Per Section:						
8 oclock all primaries						
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:						
70.0 all sections						
Terminal Type And Quantity:						
17 turret						

N/a

Shelf Life:

## NSN 5905-00-688-7013

Precision Wire Wound Variable Resistor - Page 3 of 3



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A002a0