NSN 5905-00-689-3637

Film Fixed Resistor Network - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-00-689-3637 |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -25.0/+25.0 |
| Electrical Resistance: |
| 18.000 kilohms |
| Resistance Tolerance In Percent: |
| -0.010/+0.010 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 105.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 175.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+105.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Quantity: |
| 5 |
| Terminal Type: |
| Pin |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 0.100 |
| Terminal Length: |
| 0.500 inches |
| Body Length: |
| Between 0.770 inches and 0.830 inches |
| Body Width: |
| Between 0.570 inches and 0.630 inches |
| Body Height: |
| Between 0.180 inches and 0.210 inches |
| Schematic Diagram Designator: |
| Balanced ladder network |
| Power Dissipation Rating In Watts: |
| 0.100 total network |
| Cubic Measure: |
| 0.110 cubic inches |
| Identical Value Resistor Quantity: |
| 1 highest resistance value |
| Style Designator: |
| Dual inline |
| Shelf Life: |

N/a

NSN 5905-00-689-3637

Film Fixed Resistor Network - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A001a0