NSN 5905-00-690-5684

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-690-5684

Santian Oversitive
Section Quantity:
1 Parts States
Body Style:
Cylindrical hole/slot mounted
Reliability Indicator:
Not established
Body Diameter:
1.750 inches
Shaft Diameter:
0.375 inches
Shaft Length:
1.000 inches
Body Length:
0.812 inches
Mounting Hole/stud Circle Diameter:
0.750 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Screw Thread Diameter:
0.138 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
2
Terminal Location:
Rear-bottom
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
330.0
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 single section

Power Dissipation Rating Per Section In Watts:

5.9 free air single section

NSN 5905-00-690-5684

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0