## NSN 5905-00-690-9828

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-690-9828 **Section Quantity:** 1 **Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Body Diameter:** 1.875 inches **Shaft Diameter:** Between 0.2495 inches and 0.2500 inches **Shaft Length:** 1.188 inches **Body Length:** 4.234 inches **Mounting Hole/stud Circle Diameter:** 0.156 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity:** 3 **Terminal Location:** Radially positioned over more than half the circumference **Mounting Method:** Threaded hole **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 

30.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

9000.0

**Function Conformity Tolerance Per Section:** 

-0.05/+0.05 single section

## NSN 5905-00-690-9828

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No