

View Online at <https://aerobasegroup.com/nsn/5905-00-691-5856>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Overall Length:

0.455 inches

Terminal Length:

0.217 inches

Overall Height:

Between 0.365 inches and 0.385 inches

Overall Width:

0.447 inches

Mounting Hole Diameter:

Between 0.076 inches and 0.078 inches

Shaft Diameter:

Between 0.070 inches and 0.110 inches

Shaft Length:

Between 0.060 inches and 0.100 inches

Body Length:

Between 0.365 inches and 0.385 inches

Body Width:

0.230 inches

Body Height:

Between 0.365 inches and 0.385 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Center To Center Distance Between Terminals:

0.200 inches

Lateral Distance Between Mounting Hole Centers:

Between 0.365 inches and 0.385 inches

Mounting Facility Quantity:

2

Terminal Location:

Left adjacent side single row

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

20.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.095 inches and 0.105 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0