NSN 5905-00-693-2839

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-693-2839

Towns of the Conflict of the C
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-30.0/+30.0
Electrical Resistance:
22.000 ohms
Resistance Tolerance In Percent:
-3.000/+3.000
Heat Sink Material:
Aluminum alloy
Heat Sink Length:
6.000 inches
Heat Sink Width:
4.000 inches
Heat Sink Height:
2.000 inches
Heat Sink Thickness:
0.040 inches
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
-55.0/+275.0
-55.0/+275.0 Inclosure Method:
-55.0/+275.0 Inclosure Method: Hermetically sealed
-55.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type:
-55.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Tab, solder lug
-55.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Tab, solder lug Reliability Indicator:
-55.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Tab, solder lug Reliability Indicator: Not established
-55.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length:
-55.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches
-55.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter:
-55.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches
-55.0/+275.0 Inclosure Method: Hermetically sealed Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches
Inclosure Method: Hermetically sealed Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length:
Inclosure Method: Hermetically sealed Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches Body Length:
Inclosure Method: Hermetically sealed Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches Body Length: 0.500 inches
Inclosure Method: Hermetically sealed Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 10.000 heat sink
Inclosure Method: Hermetically sealed Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts:

Aapq

NSN 5905-00-693-2839

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Style Designator:	
Axial terminal each er	nd

Reference Number Differentiating Characteristics:

As differentiated by resistance tolerence

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0