

View Online at <https://aerobasegroup.com/nsn/5905-00-697-2761>

**Section Quantity:**

3

**Reliability Indicator:**

Not established

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.875 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 3 oclock and at 9 oclock

**Nonturn Device Radius:**

0.531 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

35.000 percent, rated amperes c and better select

**Unable To Decode:**

Unable to decode and unable to decode and unable to decode

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-50.0/+50.0 2nd section

**Special Features:**

Insulated contact arm elec. Status, metallic shaft matl, fully enclosed resistive elem. Inclosure method, reliability indicator not established

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0