## NSN 5905-00-698-3608

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-698-3608 **Section Quantity:** 3 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.937 inches **Body Diameter:** Between 1.031 inches and 1.156 inches **Shaft Diameter:** Between 0.248 inches and 0.251 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** Between 1.718 inches and 1.906 inches **Overall Diameter:** 1.249 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear-bottom **Mounting Method:** Standard bushing **Features Provided: Electrical Resistance Per Section:** 

Nonmetallic shaft

Electrical Resistance Per Sec

1.000 kilohms 1st section

## NSN 5905-00-698-3608

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dis	ssipation	Rating	Per	Sectio	n In	Watts:

2.0 free air all sections

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

**Standard Taper Curve Per Section:** 

A all sections

**Terminal Type And Quantity:** 

9 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A002a0