## NSN 5905-00-700-7403

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-700-7403

**Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.125 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.875 inches **Shaft Style:** Round, slotted **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section

**Switch Current Type And Rating In Amps:** 

3.000 ac/dc

**Standard Taper Curve Per Section:** 

A single section

## NSN 5905-00-700-7403

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0