Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-701-4224

Section Quantity:

1

Body Style: Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

1.300 inches

Overall Height:

Between 0.305 inches and 0.325 inches

Overall Width:

Between 0.290 inches and 0.300 inches

Mounting Hole Diameter:

Between 0.087 inches and 0.100 inches

Shaft Diameter:

0.115 inches

Shaft Length:

Between 0.045 inches and 0.055 inches

Body Length:

Between 1.218 inches and 1.282 inches

Body Width:

Between 0.290 inches and 0.300 inches

Body Height:

Between 0.305 inches and 0.325 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Fragility Factor:

Moderately delicate

Lateral Distance Between Mounting Hole Centers:

Between 0.985 inches and 1.015 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

1.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

9000.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
200.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0 to 250.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
125.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0