

View Online at <https://aerobasegroup.com/nsn/5905-00-701-4269>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

3.156 inches

First Flat Length:

0.343 inches

Flat Height:

0.219 inches

Body Diameter:

1.875 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.125 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.750 inches

Overall Diameter:

1.876 inches

Shaft Style:

Round, flatted

Switch Type:

Toggle

Switch Voltage Rating In Volts:

120.0

Contact Arm Electrical Off Position:

Fully ccw

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.500 inches

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Double pole, double throw

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

250.000 ohms all sections

Rotary Actuator Travel In Angular Deg:

Between 265.0 and 305.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 all sections

Power Dissipation Rating Per Section In Watts:

25.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections

Switch Current Type And Rating In Amps:

0.220 ac

Standard Taper Curve Per Section:

A all sections

Special Features:

Split resistance element

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0