NSN 5905-00-701-4273

Section Quantity:

Reliability Indicator:

Not established

Overall Height:

0.516 inches

Overall Width:

0.250 inches

Rectangular w/mounting holes/slots

Body Style:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-701-4273

Mounting Hole Diameter:											
Between 0.078 inches and 0.109 inches											
Shaft Diameter:											
0.125 inches											
Shaft Length:											
0.062 inches											
Body Length:											
Between 1.234 inches and 1.266 inches											
Body Width:											
Between 0.234 inches and 0.266 inches											
Body Height:											
Between 0.312 inches and 0.344 inches											
Shaft Style:											
Round, slotted											
Actuator Type:											
Single shaft											
Center To Center Distance Between Terminals:											
0.500 inches											
Fragility Factor:											
Moderately delicate											
Lateral Distance Between Mounting Hole Centers:											
Between 0.995 inches and 1.005 inches											
Mounting Facility Quantity:											
2											
Terminal Location:											
Lower adjacent side single row											
Mounting Method:											
Unthreaded hole											
Electrical Resistance Per Section:											
2.5 megohms single section											
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:											
125.0 single section											

NSN 5905-00-701-4273

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



,	O١	W	er	Di	SS	ipa	tior	ı Ra	iting	Per	Sec	tion	In	Wat	ts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A002a0