## NSN 5905-00-701-5755

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-701-5755 **Section Quantity: Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Terminal Length:** 6.000 inches **Mounting Hole Diameter:** Between 0.088 inches and 0.098 inches **Shaft Diameter:** Between 0.100 inches and 0.130 inches Shaft Length: Between 0.060 inches and 0.080 inches **Body Length:** Between 1.240 inches and 1.260 inches **Body Width:** Between 0.180 inches and 0.200 inches **Body Height:** Between 0.300 inches and 0.330 inches **Shaft Style:** Round, slotted **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 6120.0 and 9720.0 **Maximum Starting Torque:** 8.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 50.000 ohms single section

Rotary Actuator Travel In Angular Deg:

Between 6120.0 and 9720.0

## NSN 5905-00-701-5755

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-milr27208-8 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: