NSN 5905-00-701-5958

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-701-5958 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.145 inches **Terminal Length:** 0.188 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.124 inches **Shaft Length:** Between 0.656 inches and 0.719 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** Between 1.448 inches and 1.466 inches **Overall Diameter:** 1.062 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.0005 inches

Lateral Runout: 0.003 inches

NSN 5905-00-701-5958 Precision Wire Wound Variable Resistor - Page 2 of 3



Pilot Diameter Runout:
0.00100 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-0.0/+130.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

NSN 5905-00-701-5958

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0