## NSN 5905-00-702-0465

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-702-0465

Section Quantity:
1
Reliability Indicator:
Not established
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Shaft Style:
Round, slotted
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally closed
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
250.000 ohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Switch Current Type And Rating In Amps:
3.000 ac and 3.000 dc
Standard Taper Curve Per Section:

A single section

## NSN 5905-00-702-0465

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quanti	ty	:
--------------------------	----	---

3 tab, solder lug and 3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0