NSN 5905-00-702-0465

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-702-0465

| Section Quantity: |
|--|
| 1 |
| Reliability Indicator: |
| Not established |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 0.625 inches |
| Shaft Style: |
| Round, slotted |
| Switch Type: |
| Rotary |
| Switch Voltage Rating In Volts: |
| 125.0 |
| Actuator Type: |
| Single shaft |
| Nonturn Device Location: |
| At 9 oclock |
| Nonturn Device Radius: |
| 0.531 inches |
| Switch Operating Position: |
| Start of rotation |
| Switch Contact Arrangement: |
| Single pole, single throw, normally closed |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 250.000 ohms single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0 to 10.0 single section |
| Switch Current Type And Rating In Amps: |
| 3.000 ac and 3.000 dc |
| Standard Taper Curve Per Section: |
| |

A single section

NSN 5905-00-702-0465

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Terminal Type And Quan | tity: |
|------------------------|-------|
|------------------------|-------|

3 tab, solder lug and 3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0