

View Online at <https://aerobasegroup.com/nsn/5905-00-702-4986>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.87500 inches

Pilot Length:

0.06200 inches

Undercut Diameter:

0.875 inches

Undercut Width:

0.06200 inches

Body Diameter:

Between 0.995 inches and 1.005 inches

Angle Of Mounting Hole In Deg:

30.0

Angle Between Centerlines Of Mounting Holes In Deg:

120.0

Shaft Diameter:

Between 0.245 inches and 0.255 inches

Shaft Length:

Between 0.594 inches and 0.656 inches

Body Length:

Between 1.563 inches and 1.583 inches

Mounting Lip Diameter:

1.00000 inches

Mounting Lip Depth:

0.06800 inches

Mounting Hole/stud Circle Diameter:

0.112 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3610.0

Maximum Starting Torque:

0.40 inch-ounces

Maximum Running Torque:

0.30 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.00200 inches

Shaft Radial Play:

0.002 inches

Screw Thread Diameter:

0.112 inches

Screw Thread Series Designator:

Unc

Screw Thread Qty Per Inch (tpi):

40.0

Mounting Facility Quantity:

3

Terminal Location:

Upper adjacent side single row

Mounting Method:

Threaded hole

Electrical Resistance Per Section:

5.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 3600.0 and 3610.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

3.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0