NSN 5905-00-702-4986

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-702-4986 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.87500 inches Pilot Length: 0.06200 inches **Undercut Diameter:** 0.875 inches **Undercut Width:** 0.06200 inches **Body Diameter:** Between 0.995 inches and 1.005 inches **Angle Of Mounting Hole In Deg:** 30.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** Between 0.245 inches and 0.255 inches **Shaft Length:** Between 0.594 inches and 0.656 inches **Body Length:** Between 1.563 inches and 1.583 inches **Mounting Lip Diameter:** 1.00000 inches **Mounting Lip Depth:** 0.06800 inches **Mounting Hole/stud Circle Diameter:** 0.112 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3610.0 **Maximum Starting Torque:** 0.40 inch-ounces

Maximum Running Torque:

0.30 inch-ounces

NSN 5905-00-702-4986

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.00500 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.00200 inches
Shaft Radial Play:
0.002 inches
Screw Thread Diameter:
0.112 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
40.0
Mounting Facility Quantity:
3
Terminal Location:
Upper adjacent side single row
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3610.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

NSN 5905-00-702-4986

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity	/ :
----------------------------	------------

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0