

View Online at <https://aerobasegroup.com/nsn/5905-00-702-5350>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.500 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.500 inches

Body Length:

0.453 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Maximum Stop Torque:

48.00 inch-ounces

Nonturn Device Location:

At 10 oclock and at 4 oclock

Nonturn Device Radius:

0.245 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

5.000 kilohms single section

Resistance Temperature Characteristic Range Per Section In Percent:

-3.0 to 0.0 -55 degrees celsius single section and -5.0 to 10.0 -25 degrees celsius single section and -5.0 to 10.0 25 degrees celsius single section and +0.0 to 3.0 120 degrees celsius single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0