Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-702-5629

## Section Quantity:

2

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Body Diameter:**

1.160 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.750 inches

#### Mounting Bushing Length:

0.380 inches

#### Body Length:

#### 1.260 inches

Shaft Style:

#### Round

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

312.0

#### Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# **Mounting Method:**

Standard bushing

# **Electrical Resistance Per Section:**

100.000 kilohms 1st section

# Rotary Actuator Travel In Angular Deg:

312.0

# Power Dissipation Rating Per Section In Watts:

1.4 free air all sections



Resistance Tolerance Per Section In Percent: -20.0 to 20.0 1st section Actuator Travel Control Feature: Stops Standard Taper Curve Per Section: A all sections Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig:

A002a0