## NSN 5905-00-702-6671

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-702-6671

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-20.0/+20.0
Electrical Resistance:
17.410 kilohms
Resistance Tolerance In Percent:
-0.100/+0.100
Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
145.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-65.0/+145.0
Inclosure Method:
Hermetically sealed
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
0.375 inches
Body Diameter:
0.562 inches
Body Length:
1.000 inches
Power Dissipation Rating In Watts:
0.500 free air
Terminal Width:
0.188 inches
Cubic Measure (non-core):
0.040 cubic inches
Special Features:
Resistant to humidity and salt water immersion
Unpackaged Unit Weight:
10.0 grams
Style Designator:
Radial terminal each end
Test Data Document:
81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:

N/a

Shelf Life:

81349-mil-r-93/4 government specification

## NSN 5905-00-702-6671

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0