Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-703-0905

## Section Quantity:

1

Body Style:

Cylindrical friction mounted

### **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.325 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.250 inches

#### Body Length:

0.240 inches

#### Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

310.0

#### **Terminal Location:**

Rear end

#### Mounting Method:

Terminal

#### **Features Provided:**

Nonmetallic shaft

#### **Electrical Resistance Per Section:**

2.000 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

360.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

# Power Dissipation Rating Per Section In Watts:

1.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

# Actuator Travel Control Feature:

Continuous motion

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A002a0