Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-703-8609

Section Quantity:	
1	
Body Style:	
Cylindrical	

#### **Reliability Indicator:**

Not established

#### **Terminal Length:**

0.078 inches

#### **Body Diameter:**

1.000 inches

**Body Length:** 

0.875 inches

#### Actuator Type:

Flush drive with slot-hole

# Effective Electrical Rotation In Deg Angular Rotation:

300.0

# **Center To Center Distance Between Terminals:**

0.750 inches

#### **Terminal Location:**

Front end

# Mounting Method:

Terminal

#### **Electrical Resistance Per Section:**

10.000 ohms single section

# Rotary Actuator Travel In Angular Deg:

300.0

# Center To Center Distance Between Center Terminal And Outside Terminal:

0.500 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-1.0 to 1.0 single section

# **Actuator Travel Control Feature:**

Stops

# Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 single section

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

#### Standard Taper Curve Per Section:

A single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0