

View Online at <https://aerobasegroup.com/nsn/5905-00-703-8903>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

1.3125 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

1.312 inches

**Undercut Width:**

0.0780 inches

**Body Diameter:**

1.750 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.469 inches

**Body Length:**

1.062 inches

**Mounting Lip Diameter:**

1.4370 inches

**Mounting Lip Depth:**

0.0930 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

356.0

**Maximum Starting Torque:**

1.50 inch-ounces

**Maximum Running Torque:**

0.50 inch-ounces

**Shaft End Play:**

0.00250 inches

**Shaft Runout:**

0.001 inches

**Lateral Runout:**

0.001 inches

**Pilot Diameter Runout:**

0.00250 inches

**Shaft Radial Play:**

0.001 inches

**Terminal Location:**

Rear end

**Mounting Method:**

Clamp ring

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

24.000 kilohms single section

**Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:**

15.0 single section and 30.0 single section and 45.0 single section and 60.0 single section and 75.0 single section and 90.0 single section and 105.0 single section and 120.0 single section and 135.0 single section and 150.0 single section and 165.0 single section and 180.0 single section and 195.0 single section and 210.0 single section and 225.0 single section and 240.0 single section and 255.0 single section and 270.0 single section and 285.0 single section and 300.0 single section and 315.0 single section and 330.0 single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.15/+0.15 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

4.5 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Fixed Tap Quantity Per Section:**

22 single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Terminal Type And Quantity:**

25 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Fig:**

A002a0