NSN 5905-00-704-1604

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-704-1604

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.625 inches
Terminal Length:
0.125 inches
Body Diameter:
0.500 inches
Body Length:
0.500 inches
Overall Diameter:
0.500 inches
Actuator Type:
Integral knob with counter
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Features Provided:
Hermetically sealed
Electrical Resistance Per Section:
1.040 kilohms single section
Rotary Actuator Travel In Angular Deg:
320.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-55.0 to 55.0 single section
Actuator Travel Control Feature:
Chama

Stops

NSN 5905-00-704-1604

Demilitarization:

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Precious Material:
Gold and silver
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure: