## NSN 5905-00-704-9707

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-704-9707

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.9688 inches
Pilot Length:
0.0620 inches
Overall Length:
2.331 inches
Undercut Diameter:
0.9688 inches
Undercut Width:
0.0620 inches
<b>Body Diameter:</b>
1.062 inches
Shaft Diameter:
0.1249 inches
Shaft Length:
0.375 inches
Body Length:
1.766 inches
Overall Diameter:
1.062 inches
Mounting Lip Diameter:
1.0620 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
0.75 inch-ounces
Maximum Running Torque:

0.75 inch-ounces

## NSN 5905-00-704-9707

Precision Wire Wound Variable Resistor - Page 2 of 3



Obeti Ford Plans
Shaft End Play:
0.00500 inches
Shaft Radial Play:
0.001 inches
Fragility Factor:
Moderately delicate
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.05/+0.05 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section absolute linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-5.0/+5.0 ohms single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Tap Location From Ccw Terminal Per Section In Ohms:
2500.0 single section
Function Characteristic Per Section:
Single section table
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Test Data Document:
78022-114b7041 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

No

## NSN 5905-00-704-9707

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0