## NSN 5905-00-705-7408

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-705-7408 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.7495 inches and 0.7500 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.750 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 1.245 inches and 1.250 inches **Shaft Length:** Between 0.781 inches and 0.843 inches **Body Length:** 1.800 inches **Overall Diameter:** 0.875 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 1.50 inch-ounces **Maximum Running Torque:** 

1.50 inch-ounces

**Maximum Stop Torque:** 

80.00 inch-ounces

## NSN 5905-00-705-7408

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.001 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Mechanical Backlash In Deg Angular Rotation:
0.1
Fragility Factor:
Moderately rugged
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.075/+0.075 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
185.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-350.0/+350.0 single section
Power Dissipation Rating Per Section In Watts:
0.08 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
125.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a

## NSN 5905-00-705-7408

Precision Nonwire Wound Variable Resistor - Page 3 of 3



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0