Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-705-7408

View Online at https://aerobasegroup.com/nsn/5905-00-705-740
Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 0.7495 inches and 0.7500 inches
Pilot Length:
0.0620 inches
Undercut Diameter:
0.750 inches
Undercut Width:
0.0620 inches
Body Diameter:
0.875 inches
Shaft Diameter:
Between 1.245 inches and 1.250 inches
Shaft Length:
Between 0.781 inches and 0.843 inches
Body Length:
1.800 inches
Overall Diameter:
0.875 inches
Mounting Lip Diameter:
0.8750 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
1.50 inch-ounces
Maximum Running Torque:
1.50 inch-ounces
Maximum Stop Torque:
PO 00 inch ounces

80.00 inch-ounces

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Shaft End Play: 0.001 inches Shaft Runout: 0.001 inches Lateral Runout: 0.001 inches **Pilot Diameter Runout:** 0.001 inches Shaft Radial Play: 0.001 inches Mechanical Backlash In Deg Angular Rotation: 0.1 **Fragility Factor:** Moderately rugged **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 10.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.075/+0.075 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 185.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -350.0/+350.0 single section **Power Dissipation Rating Per Section In Watts:** 0.08 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 125.0 single section **Terminal Type And Quantity:** 3 turret Shelf Life:

N/a

NSN 5905-00-705-7408

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0