NSN 5905-00-706-0393

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-706-0393 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.469 inches **Shaft Style:** Round Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 275.0 **Maximum Stop Torque:** 4.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.245 inches **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.250 inches

Screw Thread Series Designator: Unef

NSN 5905-00-706-0393

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

