NSN 5905-00-707-0806 Precision Wire Wound Variable Resistor - Page 1 of 3



recision while would variable resistor if age i
View Online at https://aerobasegroup.com/nsn/5905-00-707-0806
Section Quantity:
2
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.7500 inches
Pilot Length:
0.0930 inches
Overall Length:
4.110 inches
Undercut Diameter:
1.825 inches
Undercut Width:
0.0620 inches
Body Diameter:
2.000 inches
Angle Of Mounting Hole In Deg:
90.0
Angle Between Centerlines Of Mounting Holes In Deg:
120.0
Shaft Diameter:
0.250 inches
Shaft Length:
0.938 inches
Body Length:
4.048 inches
Overall Diameter:
2.000 inches
Mounting Lip Diameter:
2.0000 inches
Mounting Lip Depth:
0.0620 inches
Mounting Hole/stud Circle Diameter:
0.937 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball

**Actuator Type:** Single shaft

## NSN 5905-00-707-0806

Precision Wire Wound Variable Resistor - Page 2 of 3



Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
2.00 inch-ounces
Maximum Running Torque:
1.50 inch-ounces
Shaft End Play:
0.00500 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.00100 inches
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.000 kilohms all sections
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.025/+0.025 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 all sections
Power Dissipation Rating Per Section In Watts:
5.0 free air all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections

Stops

**Actuator Travel Control Feature:** 

## NSN 5905-00-707-0806

Precision Wire Wound Variable Resistor - Page 3 of 3



## **Function Characteristic Per Section:**

All sections linear

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-25.0/+25.0 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

**Terminal Type And Quantity:** 

6 tab, solder lug

Shelf Life:

Unit Of Measure:

--

N/a

Demilitarization:

No

Fiig:

A002a0