

View Online at <https://aerobasegroup.com/nsn/5905-00-708-3660>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**First Flat Length:**

0.500 inches

**Flat Height:**

0.216 inches

**Body Diameter:**

2.250 inches

**Shaft Diameter:**

Between 0.248 inches and 0.280 inches

**Shaft Length:**

0.830 inches

**Mounting Bushing Length:**

0.380 inches

**Body Length:**

1.297 inches

**Shaft Style:**

Round, flatted

**Shaft Bearing Type:**

Sleeve

**Switch Type:**

Rotary

**Switch Voltage Rating In Volts:**

28.0

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 12 oclock

**Switch Operating Position:**

Start of rotation

**Fragility Factor:**

Moderately rugged

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Lower adjacent side single row

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Cubic Measure:**

5.157 cubic inches

**Electrical Resistance Per Section:**

160.0 percent, rated amperes c and better flooring

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Actuator Travel Control Feature:**

Stops

**Switch Current Type And Rating In Amps:**

5.000 dc

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0