

View Online at <https://aerobasegroup.com/nsn/5905-00-708-3660>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

First Flat Length:

0.500 inches

Flat Height:

0.216 inches

Body Diameter:

2.250 inches

Shaft Diameter:

Between 0.248 inches and 0.280 inches

Shaft Length:

0.830 inches

Mounting Bushing Length:

0.380 inches

Body Length:

1.297 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Sleeve

Switch Type:

Rotary

Switch Voltage Rating In Volts:

28.0

Actuator Type:

Single shaft

Nonturn Device Location:

At 12 oclock

Switch Operating Position:

Start of rotation

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Lower adjacent side single row

Mounting Method:

Standard bushing

Features Provided:

Switch

Cubic Measure:

5.157 cubic inches

Electrical Resistance Per Section:

160.0 percent, rated amperes c and better flooring

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Switch Current Type And Rating In Amps:

5.000 dc

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0