Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-708-7107

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

# **Reliability Indicator:**

Not established

## Mounting Hole Diameter:

0.088 inches

#### Shaft Diameter:

0.100 inches

- Shaft Length:
- 0.060 inches

Body Length:

#### 1.250 inches

Body Width:

## 0.220 inches

Body Height:

0.310 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

9000.0

## Lateral Distance Between Mounting Hole Centers:

1.000 inches

**Mounting Facility Quantity:** 

2

Terminal Location:

Rear end

#### **Mounting Method:**

Unthreaded hole

#### **Electrical Resistance Per Section:**

1.000 kilohms single section

## Rotary Actuator Travel In Angular Deg:

9000.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-200.0 to 200.0 single section

## Power Dissipation Rating Per Section In Watts:

0.5 free air single section



## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

### Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

**Demilitarization:** 

No

Fiig:

A002a0