NSN 5905-00-709-6917

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-709-6917 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.313 inches **Overall Height:** 0.312 inches **Overall Width:** 0.250 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.188 inches **Shaft Length:** 0.063 inches **Body Length:** 1.250 inches **Body Width:** 0.250 inches **Body Height:** 0.312 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:**

Unthreaded hole
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
2.000 kilohms single section

NSN 5905-00-709-6917

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
75.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
.0 free air single section
Resistance Tolerance Per Section In Percent:
10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Precious Material And Location:
Ferminals gold
Precious Material:
Gold
Test Data Document:
20418-es1642-202I drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Ferminal Type And Quantity:
B wire lead
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A002a0