Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-709-8638

# Section Quantity:

2

Body Style:

Cylindrical hole/slot mounted

# **Reliability Indicator:**

Not established

## **Body Diameter:**

0.875 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.000 inches

**Body Length:** 

0.495 inches

## Mounting Hole/stud Circle Diameter:

# 0.475 inches

Shaft Style:

Round

## Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

360.0

## Screw Thread Diameter:

0.112 inches

## Screw Thread Series Designator:

Unc

# Screw Thready Qty Per Inch (tpi):

40.0

# Mounting Facility Quantity:

2

## **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Threaded hole

## **Electrical Resistance Per Section:**

20.000 kilohms all sections

# **Rotary Actuator Travel In Angular Deg:**

360.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

# Power Dissipation Rating Per Section In Watts:

5.0 free air all sections



Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 all sections

# Actuator Travel Control Feature:

Continuous motion

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 clamp

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0