NSN 5905-00-710-8338

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-710-8338

view Online at https://aerobasegroup.com/hsn/5905-00-710-6336
Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
Between 0.679 inches and 0.741 inches
Terminal Length:
Between 0.484 inches and 0.516 inches
Body Diameter:
0.500 inches
Body Length:
Between 0.195 inches and 0.225 inches
Actuator Type:
Flush drive with slot-hole
Maximum Starting Torque:
5.00 inch-ounces
Maximum Stop Torque:
20.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.190 inches and 0.210 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
50.000 ohms single section
Rotary Actuator Travel In Angular Deg:
285.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.090 inches and 0.110 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:

Stops

NSN 5905-00-710-8338

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Screwdriver slot adjustment
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No