## NSN 5905-00-711-0617

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-711-0617 **Section Quantity: Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.455 inches **Overall Height:** Between 0.370 inches and 0.380 inches **Overall Width:** Between 0.185 inches and 0.195 inches **Mounting Hole Diameter:** Between 0.072 inches and 0.082 inches **Shaft Diameter:** 0.093 inches **Shaft Length:** 0.080 inches **Body Length:** Between 0.370 inches and 0.380 inches **Body Width:** Between 0.185 inches and 0.195 inches **Body Height:** Between 0.370 inches and 0.380 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 8280.0 and 9720.0 **Maximum Starting Torque:** 5.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** Between 0.370 inches and 0.380 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole

**Electrical Resistance Per Section:** 

500.0 ohms single section

## NSN 5905-00-711-0617

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## **Rotary Actuator Travel In Angular Deg:** Between 8280.0 and 9720.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -70.0 to 70.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** Sealed to permit cleaning in common solvents **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:**