NSN 5905-00-714-3816

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-714-3816

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Shaft Diameter:
0.125 inches
Shaft Length:
0.500 inches
Body Length:
8.025 inches
Body Width:
0.880 inches
Body Height:
1.000 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Fragility Factor:
Moderately delicate
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Terminal
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

NSN 5905-00-714-3816

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A single section
Special Features:
Shaft has a flexible section, also a wrench flat and a rd slotted end. Mounting holes are 0.194 in diameter and 7.150 in c to c
Ferminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-

Demilitarization:

No

Fiig:

A002a0