

View Online at https://aerobasegroup.com/nsn/5905-00-716-0730

View Online at https://aerobasegroup.com/nsn/5905-00-716-0730
Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 2.8745 inches and 2.8750 inches
Pilot Length:
Between 0.0570 inches and 0.0670 inches
Undercut Diameter:
2.875 inches
Undercut Width:
0.0730 inches
Body Diameter:
2.875 inches
Shaft Diameter:
0.250 inches
Shaft Length:
Between 0.734 inches and 0.766 inches
Body Length:
0.984 inches
Mounting Lip Diameter:
Between 2.9950 inches and 3.0050 inches
Mounting Lip Depth:
Between 0.0880 inches and 0.0980 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
350.0
Maximum Starting Torque:
2.00 inch-ounces
Maximum Running Torque:
1.50 inch-ounces
Shaft End Play:
0.00500 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches



Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.05/+0.05 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
95.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
60.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0