NSN 5905-00-716-0916

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-716-0916 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.6250 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0630 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.625 inches **Body Length:** 3.250 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 1.20 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Shaft End Play:** 0.00500 inches

Shaft Runout: 0.001 inches

NSN 5905-00-716-0916

Precision Wire Wound Variable Resistor - Page 2 of 3



| Lateral Runout: |
|---|
| 0.003 inches |
| Pilot Diameter Runout: |
| 0.00150 inches |
| Shaft Radial Play: |
| 0.002 inches |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Clamp ring |
| Electrical Resistance Per Section: |
| 60.000 percent, rated amperes c and better industrial clears |
| Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: |
| 1800.0 all sections |
| Rotary Actuator Travel In Angular Deg: |
| 3600.0 |
| Function Conformity Tolerance Per Section: |
| -1.00/+1.00 all sections |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 50.0 all sections |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air all sections |
| Function Conformity Per Section: |
| All sections independent linearity |
| Fixed Tap Quantity Per Section: |
| 1 all sections |
| Tap Location Tolerance Per Section: |
| -1.0/+1.0 degrees angular rotation all sections |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 all sections |
| Actuator Travel Control Feature: |
| Stops |
| Function Characteristic Per Section: |
| All sections linear |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 25.0 all sections |
| Terminal Type And Quantity: |
| 8 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5905-00-716-0916

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0