## NSN 5905-00-716-3520

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-716-3520 **Section Quantity:** 1 **Body Style:** Cylindrical tab/flange mounted **Reliability Indicator:** Not established **Body Diameter:** 0.625 inches **Mounting Hole Diameter:** 0.156 inches **Body Length:** 0.750 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Fragility Factor:** Moderately delicate **Lateral Distance Between Mounting Hole Centers:** 1.375 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 500.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 260.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 0.1 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

C single section

## NSN 5905-00-716-3520

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A002a0