Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-00-716-5931

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

## **Reliability Indicator:**

Not established

#### Mounting Hole Diameter:

0.086 inches

#### Shaft Diameter:

0.125 inches

- Shaft Length:
- 0.063 inches

#### Body Length:

1.250 inches

#### Body Width:

0.500 inches

# Body Height:

0.312 inches

Shaft Style:

Round

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

#### Lateral Distance Between Mounting Hole Centers:

1.000 inches

#### **Mounting Facility Quantity:**

2

#### Terminal Location:

Rear end

#### **Mounting Method:**

Unthreaded hole

#### **Electrical Resistance Per Section:**

2.000 kilohms single section

#### Rotary Actuator Travel In Angular Deg:

9000.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

135.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

## Power Dissipation Rating Per Section In Watts:

0.5 free air single section



#### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

#### Actuator Travel Control Feature:

Clutch

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0