

View Online at <https://aerobasegroup.com/nsn/5905-00-717-7673>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.8750 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

2.000 inches

Undercut Width:

0.0930 inches

Body Diameter:

2.000 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.438 inches

Body Length:

2.250 inches

Mounting Lip Diameter:

2.0000 inches

Mounting Lip Depth:

0.0730 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Shaft Runout:

0.001 inches

Lateral Runout:

0.001 inches

Pilot Diameter Runout:

0.00200 inches

Shaft Radial Play:

0.001 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.05/+0.05 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

0.17 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0