NSN 5905-00-719-9469

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-719-9469 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 1.739 inches **Undercut Diameter:** 0.875 inches **Undercut Width:** 0.0600 inches **Body Diameter:** 1.000 inches **Shaft Diameter:** 0.1247 inches **Shaft Length:** 0.656 inches **Body Length:** 0.859 inches **Mounting Lip Diameter:** 1.0000 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:**

0.50 inch-ounces

Shaft End Play:
0.005 inches

NSN 5905-00-719-9469

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
4.5 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-400.0/-300.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section absolute conformity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section 360 degrees sine-cosine
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Test Data Document:
81413-116020-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
6 turret
Shelf Life:
N/a
Unit Of Measure:

NSN 5905-00-719-9469

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0