Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-721-0263

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Overall Length:**

1.484 inches

#### Body Diameter:

1.094 inches

#### Shaft Diameter:

0.250 inches

### Shaft Length:

0.875 inches

### Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

0.609 inches

### Shaft Style:

Round, slotted

# Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

Between 309.0 and 320.0

#### Maximum Starting Torque:

6.00 inch-ounces

#### Maximum Running Torque:

6.00 inch-ounces

#### Maximum Stop Torque:

128.00 inch-ounces

#### Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

0.531 inches

#### Fragility Factor:

Moderately rugged

## Screw Thread Diameter:

0.375 inches

# Screw Thread Series Designator:

Unef

AeroBase Group

Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

**Electrical Resistance Per Section:** 

500.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 309.0 and 320.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

### **Test Data Document:**

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

3 tab, solder lug

**Specification Data:** 

81349-mil-r-94/5 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0