NSN 5905-00-721-0388

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-721-0388

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-20.0/+20.0
Electrical Resistance:
6.000 kilohms
Resistance Tolerance In Percent:
-5.000/+5.000
Heat Sink Material:
Steel
Heat Sink Length:
12.000 inches
Heat Sink Width:
12.000 inches
Heat Sink Thickness:
0.059 inches
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
265.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
Inclosure Method:
Inclosure Method: Encased
Encased
Encased Terminal Type:
Encased Terminal Type: Tab, solder lug
Encased Terminal Type: Tab, solder lug Reliability Indicator:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.430 inches
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.430 inches Body Diameter:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.430 inches Body Diameter: 0.870 inches
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.430 inches Body Diameter: 0.870 inches Mounting Bushing Length:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.430 inches Body Diameter: 0.870 inches Mounting Bushing Length: 0.808 inches
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.430 inches Body Diameter: 0.870 inches Mounting Bushing Length: 0.808 inches Body Length:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.430 inches Body Diameter: 0.870 inches Mounting Bushing Length: 0.808 inches Body Length: 0.812 inches
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.430 inches Body Diameter: 0.870 inches Mounting Bushing Length: 0.808 inches Body Length: 0.812 inches Power Dissipation Rating In Watts:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.430 inches Body Diameter: 0.870 inches Mounting Bushing Length: 0.808 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 12.500 free air
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.430 inches Body Diameter: 0.870 inches Mounting Bushing Length: 0.808 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 12.500 free air Mounting Bushing Diameter:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.430 inches Body Diameter: 0.870 inches Mounting Bushing Length: 0.808 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 12.500 free air Mounting Bushing Diameter: 0.625 inches

N/a

NSN 5905-00-721-0388

Inductive Wire Wound Fixed Resistor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0