NSN 5905-00-721-0879

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-721-0879

Section Quantity:
1
Body Style:
Rectangular w/bushing/holes/slots
Reliability Indicator:
Not established
Thread Length:
0.900 inches
Shaft Diameter:
0.188 inches
Shaft Length:
3.250 inches
Mounting Bushing Length:
1.000 inches
Body Length:
3.750 inches
Body Width:
0.750 inches
Body Height:
0.688 inches
Shaft Style:
Round, threaded
Actuator Type:
Single shaft
Lateral Distance Between Mounting Hole Centers:
3.500 inches
Screw Thread Diameter:
0.112 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
40.0
Mounting Facility Quantity:
4
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
10.000 kilohms single section
Function Conformity Tolerance Per Section:

-1.00/+1.00 single section

NSN 5905-00-721-0879

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
105.0 single section
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No